

archlit reserves the right to make changes without prior notice. (01.11.2016)

Minuet is a series of square trimless recessed downlights in aluminum injection. Damp location certified. A frame in polycarbonate for the frosted diffuser in white. The standard option for the diffuser is flood illumination, special optics with different aperture reflectors can be specified. In case of service of the lighting modules, they can be removed with no tooling. Dimmable and non dimmable, in 2700 K and 3000K. Once installed in the housing, the square can be aligned and fixed in a position by tightening one screw for later mud at sides. High power versions replace HID sources, are dimmable, and on /off with no delays on restarting. These options can be connected to control systems and occupancy sensors.

MT.5 Minuet Recessed Downlight Trimless

Lumen Output

24 - 2,400 lumens 2700k 20w 350 mA

25 - 2,500 lumens 3000k 20w 350 mA

44 - 4,400 lumens 2700k 39w 700 mA

47 - 4,700 lumens 3000k 39w 700 mA

Dimming

O - Non Dimmable 120v

1 - Non Dimmable 277v

2 - Dim TRIAC 120v

3 - Dim TRIAC 277V

4 - Dim 0-10v (4wires, 120v-277-v)

Housing

NC - New Construction

IC - IC Housing

Optics

28 - 28 deg beam

38 - 38 deg beam

45 - 45 deg beam

N - Frosted diffuser

Finish

WH - White

BK - Black

CU - Custom Color Specify RAL color

Emergency

00 - No Emergency

EM - Emergency

Emergency only for 350 mA (20w)

Notes:

IC Housing for 3gw, uses active heatsink. Fan incorporated with low noise (practically imperceptible), dimmable only 0-10v











